

**LED**

Norms: EN 60598-1, EN 60598-2-2



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial, Business areas, Housing, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>80, MacAdam Step <3, 80.000h lifetime (@L90, B10, Ta 25 C).

**Optical System:** Diffuser: Opal.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium and steel sheet.

**Surface Finish:** Powder coated epoxy polyester.

LIGHT+ - Opal diffuser in PMMA


	LED	UGR	W	Lm Output	Lm/W	AxB (mm)	K3	kg	HF	DALI
		≤25	17	1800	105	Ø300x85	-	-	90573.L300.E	90573.L300.H
		≤25	25	3040	122	Ø400x85	-	-	90573.L400.E	90573.L400.H
		≤25	44	6188	141	Ø600x85	•	-	90573.L600.E	90573.L600.H

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.




## COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
U	Blue
V	Green
T	Yellow
K	Red
N	Jungle
D	Golden eye
O	Sahara
L	Autumn
R	Rusty chain
C	Pure chocolate
1	Mist
9	Dark rock
I	Carbon

## DIMENSIONS



D (mm)	
Ø300	Ø286
Ø400	Ø386
Ø600	Ø586



## OPTIONS

### Colour temperature



3000K  
Tunable White

• The Tunable White option isn't available for the 300 mm diameter version.

Order code  
**3000**  
**T000**

### Emergency unit




Emergency unit 3 hours

• Prepared for Remote-control

Order code  
**K3**

### Low power version



Option supplied under request.

### Safety cable



Steel safety cable


Order Code  
**955000**

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## DETAILS




LIGHT+ diffuser



Ceiling recessed application

## PHOTOMETRY



ROFY 85 IP /E  
HO LIGHT+

### TO SPECIFY:

Recessed circular LED luminaire with IP54. Extruded aluminium frame, available in 16 different colours. Available in 5 diameters, 300, 400, 600, 900 and 1150mm, with opal acrylic diffuser (PMMA) for homogenous light diffusion. Standard version with 4000K LED, RG1 (Photobiological Risk Group 1, according to IEC 62471), CRI>80, 80.000 lifetime (@L80, B10, Ta 25 C). Available as option in 3000K, Tunable White (2700-6500K), with dimmable DALI driver and 3h emergency unit. – as Indelague ROFY 85 IP /E.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.