

LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Housing, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>80, MacAdam Step <3, 80.000h lifetime (@L90, B10, Ta 25 C).

Optical System: Diffuser: Opal.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium and steel sheet.

Surface Finish: Powder coated epoxy polyester.

LIGHT+ - Opal diffuser in PMMA


	LED	UGR	W	Lm Output	Lm/W	AxB (mm)	K3	kg	HF	DALI
		≤25	17	1800	105	Ø300x85	-	-	90573.L300.E	90573.L300.H
		≤25	25	3040	122	Ø400x85	-	-	90573.L400.E	90573.L400.H
		≤25	44	6188	141	Ø600x85	•	-	90573.L600.E	90573.L600.H

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
U	Blue
V	Green
T	Yellow
K	Red
N	Jungle
D	Golden eye
O	Sahara
L	Autumn
R	Rusty chain
C	Pure chocolate
1	Mist
9	Dark rock
I	Carbon

DIMENSIONS




D (mm)	
Ø300	Ø286
Ø400	Ø386
Ø600	Ø586



OPTIONS

Colour temperature



3000K
Tunable White

• The Tunable White option isn't available for the 300 mm diameter version.

Order code
3000
T000

Emergency unit



Emergency unit 3 hours

• Prepared for Remote-control

Order code
K3

Low power version



Option supplied under request.

Safety cable



Steel safety cable


Order Code
955000

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

DETAILS




LIGHT+ diffuser



Ceiling recessed application

PHOTOMETRY



ROFY 85 IP /E
HO LIGHT+

TO SPECIFY:

Recessed circular LED luminaire with IP54. Extruded aluminium frame, available in 16 different colours. Available in 5 diameters, 300, 400, 600, 900 and 1150mm, with opal acrylic diffuser (PMMA) for homogenous light diffusion. Standard version with 4000K LED, RG1 (Photobiological Risk Group 1, according to IEC 62471), CRI>80, 80.000 lifetime (@L80, B10, Ta 25 C). Available as option in 3000K, Tunable White (2700-6500K), with dimmable DALI driver and 3h emergency unit. – as Roxo Lighting ROFY 85 IP /E.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.