



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface/Suspended.

Light Distribution: Direct.

Light Source: T5 (G5) or TC-L (2G11) lamp.

Optical System: Diffuser: Opal polycarbonate.

Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

DOP - Opal polycarbonate diffuser

LAMP*	W	AxB (mm)	K1	K3	Kg	HF	DSI	DALI
T5	1x21 + 8x14	Ø950x85	•	•	13,8	90081.0950.A	90081.0950.G	90081.0950.D
	2x14 + 4x21 + 4x28	Ø1250x85	•	•	23,5	90081.1250.A	90081.1250.G	90081.1250.D
TC-L	2x18	Ø350x85	-	-	2,7	90081.0350.A	--	--
	2x24	Ø450x85	-	-	3,7	90081.0450.A	90081.0450.G	90081.0450.D
	3x36	Ø650x85	-	-	7,3	90081.0650.A	90081.0650.G	90081.0650.D


COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)
U	Blue (RAL 5002)
K	Red (RAL 3020)
V	Green (RAL 6018)
T	Yellow (RAL 1021)

OPTIONS

Code	Description
910700	Suspension Type "1" (x3). • Suspension kit for Ø350, Ø450, Ø650 and Ø950mm.
910701	Suspension Type "1" (x4). • Suspension kit only for Ø1250mm version.
940400	1,5m transparent current cable 3x0,75 mm ² .
940500	1,5 m transparent current cable 5x0,75 mm ² .
940600	1,5m transparent current cable 7x0,75 mm ² .
9705	Ceiling rose (x3). • Ceiling rose for Ø350, Ø450, Ø650 and Ø950mm.
9706	Ceiling rose (x4). • Ceiling rose only for Ø1250mm.
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.

DIMENSIONS



* Lamp not included.

Example code for order: 90081.1250.D (DALI) + W (COLOUR/FINISH) + 910701 + 940500 + 9706 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.


ROXO LIGHTING LIMITED

24 BEDFORD ROW | LONDON | WC1R 4TQ

roxo.london@roxolighting.com | www.roxolighting.com

PHOTOMETRY

ROFY 1x21W + 8x14W DOP
Lamp: 1 x 21W/840 + 8 x 14W/840



TO SPECIFY:

Surface or suspended T5(G5) or Compact fluorescent TC-L (2G11) luminaire with five sizes available (Ø350, Ø450, Ø650, Ø950 and Ø1250mm) and round opal polycarbonate diffuser. Optional white, grey, black, red, yellow, green or blue finish and 1 or 3 hours emergency available – as Roxo Lighting ROFY.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.