



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Sports hall.

Mounting: Surface/Suspended.

Light Distribution: Direct.

Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt (RAL9016).

ELG - White powder coated "V" shape louvre with steel rods

LAMP*	W	AxBxC (mm)	HF	DSI	DALI
T5	3x35	1497x375x85	9L5J.335.46.A4	9L5J.335.46.84	9L5J.335.46.74
	3x49	1497x375x85	9L5J.349.46.A4	9L5J.349.46.84	9L5J.349.46.74
	3x80	1497x375x85	9L5J.380.46.A4	9L5J.380.46.84	9L5J.380.46.74
	4x28	1197x487x85	9L5J.428.46.A4	9L5J.428.46.84	9L5J.428.46.74
	4x35	1497x485x85	9L5J.435.46.A4	9L5J.435.46.84	9L5J.435.46.74
	4x49	1497x485x85	9L5J.449.46.A4	9L5J.449.46.84	9L5J.449.46.74
	4x54	1197x485x85	9L5J.454.46.A4	9L5J.454.46.84	9L5J.454.46.74
	4x80	1497x485x85	9L5J.480.46.A4	9L5J.480.46.84	9L5J.480.46.74

EMG - Satin aluminium "V" shape louvre with steel rods

LAMP*	W	AxBxC (mm)	HF	DSI	DALI
T5	3x35	1497x375x85	9L5J.335.54.A4	9L5J.335.54.84	9L5J.335.54.74
	3x49	1497x375x85	9L5J.349.54.A4	9L5J.349.54.84	9L5J.349.54.74
	3x80	1497x375x85	9L5J.380.54.A4	9L5J.380.54.84	9L5J.380.54.74
	4x28	1197x487x85	9L5J.428.54.A4	9L5J.428.54.84	9L5J.428.54.74
	4x35	1497x485x85	9L5J.435.54.A4	9L5J.435.54.84	9L5J.435.54.74
	4x49	1497x485x85	9L5J.449.54.A4	9L5J.449.54.84	9L5J.449.54.74
	4x54	1197x485x85	9L5J.454.54.A4	9L5J.454.54.84	9L5J.454.54.74
	4x80	1497x485x85	9L5J.480.54.A4	9L5J.480.54.84	9L5J.480.54.74

* Lamps not included.


Example code for order: 9L5J.335.46.A4 (HF) + W5M (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS


Code	Description
W3MFC	Connector 3-pole wieland GST 18i3 male + 1m cable with 3-pole wieland GST 18i3 female
W5MFC	Connector 5-pole wieland GST 18i5 male + 1m cable with 5-pole wieland GST 18i5 female
W5MFDC	Connector 5-pole wieland GST 18i5 DIM male + 1m cable with 5-pole wieland GST 18i5 DIM female
W3M	Connector 3-pole wieland GST 18i3 male
W5M	Connector 5-pole wieland GST 18i5 male
W5MD	Connector 5-pole wieland GST 18i5 DIM male
K3	Emergency unit 3 hours
K1	Emergency unit 1 hour
SQS	Polycarbonate Lamps as optional safety cover (IK10)
910002	Suspension Type "I" (x4)
--	Lamps as optional

DETAILS



Extra protection for the reflector

DIMENSIONS



TO SPECIFY:

Surface or suspended sports hall luminaire suitable for 3x35/49/80W or 4x28/35/49/54/80W T5(G5) lamp. Optional polycarbonate safety cover, dimmable version and 1 or 3 hours emergency - as Indelague SDT.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.