
Datasheet



### DOZ - Opal polycarbonate diffuser

LED	w	Lm	mA	v	η(%)	AxB (mm)	ß	Kg	ORDER CODE
	1	101	350	3	33	Ø53x47	Ø44	0,2	90062.L101.E
	3	187	700	4	31	Ø53x47	Ø44	0,2	90062.L103.E

DOZ

To complete the product add control gear. Please order separately.

## COLOUR / FINISH

Code	Description			
W	White **			
G	Grey **			
B	Black **			

#### DETAILS



\*\* Other colours under request Example code for order: 90062.L103.E (ORDER CODE) + W (COLOUR/FINISH) + 3000 + 970200 + D3-1 (OPTIONS)

IG002EN/0

# SENSE Downlights

# Datasheet

# OPTIONS

Colour temperature			Control gear			
К	3000K 5700K	Order code 3000 5000	LED Driver 350mA for 1 downlight 1W LED Driver 700mA for 1 downlight 3W	Order co D1 D3		
nstallation housing		Order code	IP (Ingress protection)	Order co		
	Installation housing for concrete	970200	Versão IP20/65 Option supplied under request.			
PHOTOMETRY	DIMENSIONS		TO SPECIFY: Circular LED recessed downlight. Aluminium boo	ly, powder coated in		
60 <sup>°</sup> 10 <sup>°</sup>	B A 63 76	ion	epoxy polyester and opal polycarbonate DOZ diffuser. Standard total luminous flux of 101 or 187 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Optional IP20/65 version, 3000K or 5700K and installation housing for concrete as Roxo Lighting SENSE			

TIG002EN/02