



**LED**

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Wall Mounted.

**Light Source:** LED 4000K, CRI>80, 50.000h life.


**Optical System:** Diffuser: Opal polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

DOZ - Opal polycarbonate diffuser

LED	W	Lm	η(%)	AxBxC (mm)	Kg	HF	DALI
	11	1290	58	350x41x75	1,0	90182.L110.E	90182.L110.H
	23	2580	68	590x41x75	1,6	90182.L120.E	90182.L120.H

**COLOUR / FINISH**

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black
• Other colours under request.	


**DETAILS**



Product detail

**OPTIONS**

Colour temperature




3000K

Order code  
**3000**

Example code for order: 90182.L110.H (DALI) + W (COLOUR/FINISH) + 3000 (OPTIONS)


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

## PHOTOMETRY



SLIM LED 11W  
DOZ 4000K

## DIMENSIONS



## TO SPECIFY:

LED wall mounted luminaire. Standard total luminous flux of 1290 or 2580 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Direct light distribution through DOZ opal polycarbonate diffuser. Optional DALI dimmable driver and 3000K. - as Indelague SLIM LED

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.