



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Source: LED 4000K, CRI>80, 50.000h life.


Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

DOZ - Opal polycarbonate diffuser

LED	W	Lm	η(%)	AxBxC (mm)	Kg	HF	DALI
	11	1290	58	350x41x75	1,0	90182.L110.E	90182.L110.H
	23	2580	68	590x41x75	1,6	90182.L120.E	90182.L120.H

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black
• Other colours under request.	

DETAILS



Product detail

OPTIONS

Colour temperature




3000K

Order code
3000

Example code for order: 90182.L110.H (DALI) + W (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.


PHOTOMETRY




SLIM LED 11W
DOZ 4000K

DIMENSIONS

350



590



TO SPECIFY:

LED wall mounted luminaire. Standard total luminous flux of 1290 or 2580 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Direct light distribution through DOZ opal polycarbonate diffuser. Optional DALI dimmable driver and 3000K. - as Roxo Lighting SLIM LED

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.