



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: TC-DEL (G24q-2/G24q-3) lamp or TC-TEL (GX24q-3/GX24q-4) lamp.

Control Gear: Electronic equipment 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

PB - Polished aluminium louvre

LAMP*	UGR		W	η(%)	AxBxC (mm)	f	Kg	HF	DSI	DALI
TC-DEL	≤19	G24q-2	2x18	59	300x300x140	275x275	1,86	90007.E218.A	90007.E218.C	90007.E218.D
	≤19	G24q-3	2x26	58	300x300x140	275x275	1,86	90007.F226.A	90007.F226.C	90007.F226.D
TC-TEL	≤22	GX24q-3	2x32	53	300x300x140	275x275	1,86	90007.I232.A	90007.I232.C	90007.I232.D
	≤22	GX24q-4	2x42	48	300x300x140	275x275	1,86	90007.J242.A	90007.J242.C	90007.J242.D

PM - Satin aluminium louvre

LAMP*	UGR		W	η(%)	AxBxC (mm)	f	Kg	HF	DSI	DALI
TC-DEL	≤19	G24q-2	2x18	54	300x300x145	275x275	1,86	90121.E218.A	90121.E218.C	90121.E218.D
	≤19	G24q-3	2x26	54	300x300x145	275x275	1,86	90121.F226.A	90121.F226.C	90121.F226.D
TC-TEL	≤19	GX24q-3	2x32	48	300x300x145	275x275	1,86	90121.I232.A	90121.I232.C	90121.I232.D
	≤22	GX24q-4	2x42	44	300x300x145	275x275	1,86	90121.J242.A	90121.J242.C	90121.J242.D

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
003	Transparent glass.
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.
--	Lamps as optional.

DETAILS



Downlight detail

* Lamp not included.


Example code for order: 90007.J242.D (DALI) +W (COLOUR/FINISH) + 003 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.



PHOTOMETRY

DIMENSIONS

SQUARE 2x32W PB
Lamp: 2 x TC-TEL 32W/840



SQUARE 2x32W PM
Lamp: 2 x TC-TEL 32W/840



TO SPECIFY:

Recessed compact fluorescent downlight for twin 18/26W TC-DEL or 32/42W TC-TEL lamps with polished or satin aluminium louvre. Optional transparent 4mm tempered glass and 1 or 3 hours emergency available. For ceiling thicknesses of 1-25mm – as Roxo Lighting SQUARE.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.