

**LED**

Norms: EN 60598-1, EN 60598-2-1



IP 40

960°C

230V/50Hz

## PRODUCT DESCRIPTION

**Areas of Application:** Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

**Mounting:** Surface/Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 60.000h life (@L90, B10, Ta 25 C).

**Optical System:** Diffuser: Opal polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Wiring:** Pre-wired 1,5m long cable.

**Materials:** Body: Extruded aluminium profile. End caps: Injected polycarbonate.

**Surface Finish:** Anodised in natural colour.

bLINE - Opal polycarbonate diffuser




LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	K1	K3	kg	HF	DALI
	≤22	19	2656	112	80	Ø100x598	-	-	2,0	90438.L220.E	90438.L220.H
	≤22	27	3984	118	80	Ø100x878	-	-	2,7	90438.L230.E	90438.L230.H
	≤22	35	5312	123	81	Ø100x1158	•	•	3,4	90438.L240.E	90438.L240.H
	≤22	43	6640	125	81	Ø100x1438	•	•	4,2	90438.L250.E	90438.L250.H
	≤22	54	7968	117	79	Ø100x1718	•	•	4,8	90438.L260.E	90438.L260.H
	-	62	9296	120	80	Ø100x1998	•	•	6,1	90438.L270.E	90438.L270.H
	-	71	10624	121	81	Ø100x2278	•	•	6,9	90438.L280.E	90438.L280.H
	-	79	11952	123	81	Ø100x2558	•	•	7,5	90438.L290.E	90438.L290.H
	-	87	13280	124	81	Ø100x2838	•	•	8,4	90438.L200.E	90438.L200.H

## COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
•End caps finishing.	

## DIMENSIONS



Recessed ceiling rose



Surface ceiling rose



Example code for order: 90438.L200.E (HF) + W(COLOUR/FINISH) + 910409 + W(COLOUR/FINISH) + 3000 + K3(OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## OPTIONS

### Colour temperature



3000K

Order Code  
**3000**

### Ceiling rose



Ceiling rose  
Circular surface  
Circular recessed

Order Code

**9716**  
**9713**

• To order this option, please choose colour required to the ceiling rose.

### Suspension



Suspension type "I"

Order Code  
**910409**

### Fixation kit



Fixation kit

Order Code  
**9264**

• Fixation kit in injected polycarbonate.

### Emergency unit



Emergency unit 3 hours  
Emergency unit 1 hour

Order Code  
**K3**  
**K1**

•Only available for HF versions.

## DETAILS




Clip-in diffuser



Profile end caps

## PHOTOMETRY



TALEA 1438mm  
bLINE 4000K

### TO SPECIFY:

Tubular LED luminaire for surface mounted or suspended application. Body with Ø100mm, composed by an extruded aluminium profile, anodized in natural colour, and an opal polycarbonate clip-in diffuser bLINE and injected polycarbonate end caps, available in grey, white and black. Ceiling rose available in recessed and surface mounted version. Standard version in 4000K LED, CRI>80 and 60.000h lifetime (@L90, B10, Ta 25 C). DALI dimmable version available. Optional 3000K and 1h or 3h emergency unit. High output (HO) option available. – as Indelague TALEA.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.