



LED



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.

Fixing system: Brackets.


bLINE - Opal polycarbonate diffuser

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	f	K1	K3	kg	HF	DALI
LED	≤22	30	3870	85	66	848x120x98	849x102	-	-	3,8	9Z7F.130.20.F4	9Z7F.130.20.E4
	≤22	39	5160	87	66	1128x120x98	1129x102	•	•	4,3	9Z7F.140.20.F4	9Z7F.140.20.E4
	≤25	47	6450	86	63	1408x120x98	1409x102	•	•	5,3	9Z7F.150.20.F4	9Z7F.150.20.E4
	≤22	56	7740	91	66	1688x120x98	1689x102	•	•	7,6	9Z7F.160.20.F4	9Z7F.160.20.E4
	-	64	9030	93	66	1970x120x98	1971x102	•	•	8,1	9Z7F.170.20.F4	9Z7F.170.20.E4
	-	77	10320	87	65	2250x120x98	2251x102	•	•	8,6	9Z7F.180.20.F4	9Z7F.180.20.E4
	-	86	11610	88	65	2530x120x98	2531x102	•	•	9,6	9Z7F.190.20.F4	9Z7F.190.20.E4
	-	94	12900	86	63	2810x120x98	2811x102	•	•	10,6	9Z7F.100.20.F4	9Z7F.100.20.E4

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black (RAL 9005)

DIMENSIONS



Example code for order: 9Z7F.100.20.F4 (HF) + 3000 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K
Tunable White

Order code
3000
T000

Steel safety cable



Steel safety cable

Order code
955000

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

- Test function by telecommand signal.

Order code
K3
K1

Low power option



Option supplied under request.

DETAILS




Clip-in diffuser system



Bracket

PHOTOMETRY



TCH /E LED 30W
bLINE 4000K

TO SPECIFY:

Linear recessed LED luminaire, individually mounted and 112 mm width. Extruded aluminium profile, anodised in natural colour. Aluminium end caps without visible screws and polycarbonate bLINE diffuser. Standard version with 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Optional 3000K, DALI dimmable driver, TunableWhite technology and 1 or 3 hours emergency unit. – as Indelague TCH /E LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.