



Norms: EN 60598-1, EN 60598-2-2



**PRODUCT DESCRIPTION**

**Areas of Application:** Offices and Meeting rooms, Kitchen, Hospital, Restrooms, Schools, Corridors and Reception areas.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct / Indirect.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10 , Ta 25° C).

**Optical System:** Microperforated steel sheet.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated in white matt.

**Fixing system:** Brackets.

DCS - Microperforated central diffuser

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	■	K1	K3	kg	HF	DALI
LED	30	3600	76	63	595x595x95	578x578	•	•	5,1	9Z1N.213.13.F4	9Z1N.213.13.E4
	41	5400	78	59	595x595x95	578x578	•	•	5,1	9Z1N.313.13.F4	9Z1N.313.13.E4


**DETAILS**



Side fixture connector on the luminaire

**OPTIONS**


**Colour temperature**



3000K

Order code  
**3000**

**Light and presence sensor**



Option supplied under request.

Example code for order: 9Z1N.313.13.74 (DALI) + W5MD + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**Connectors**



Connector 3-pole wieland GST 18i3 male  
Connector 5-pole wieland GST 18i5 male  
Connector 5-pole wieland GST 18i5 DIM male

Order code  
**W3M**  
**W5M**  
**W5MD**

**Steel safety cable**



Steel safety cable

Order code  
**955000**

**Emergency unit**




Emergency unit 3 hours  
Emergency unit 1 hour

Order code  
**K3**  
**K1**


• Test function by telecommand signal.

**PHOTOMETRY**


**DIMENSIONS**




TEI LED 30W  
DCS 4000K




**FIXING SYSTEMS**



Pull-up version with brackets for plasterboard ceilings



Pull-up version with brackets for exposed T grids 15/24mm



Lay-in version for exposed T grids 15/24mm

**TO SPECIFY:**

Recessed indirect LED luminaire for modular ceilings application. Micro-perforated central diffuser. Standard version with 4000K LED, CRI>80 and 50.000h lifetime (@L80,B10, Ta 25 C). Optional LED dimmable Dali driver. Available in 3000K, with fast connectors, light and presence sensor and emergency 1 and 3 hour units. Available to be installed in exposed T grids 15/24mm, or with brackets - as Indelague TEI LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.