



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 65.000h lifetime (@L80,B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Wiring: Pre-wired 1,5m transparent cable.

Materials: Extruded aluminium.

Surface Finish: Anodised in natural colour.

DAM - Microprismatic diffuser


LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	≤19	30	4080	91	67	915x370x58	8,2	9YDD.130.6V.F4	9YDD.130.6V.E4
	≤19	39	5440	95	68	1185x370x58	10,5	9YDD.140.6V.F4	9YDD.140.6V.E4
	≤19	47	6800	94	65	1460x370x58	11,1	9YDD.150.6V.F4	9YDD.150.6V.E4
	≤19	39	5540	95	68	640x640x58	9,2	9YDD.410.6V.F4	9YDD.410.6V.E4

DOZ - Opal polycarbonate diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	≤22	30	4440	86	63	915x370x58	8,2	9YDD.130.2J.F4	9YDD.130.2J.E4
	≤22	39	5440	88	63	1185x370x58	10,5	9YDD.140.2J.F4	9YDD.140.2J.E4
	≤22	47	6800	91	63	1460x370x58	11,1	9YDD.150.2J.F4	9YDD.150.2J.E4
	≤22	39	5440	92	66	640x640x58	9,2	9YDD.410.2J.F4	9YDD.410.2J.E4

Please note:
DAM | DOZ
• To complete the product add suspension and ceiling rose. Please order separately.

DIMENSIONS



Example code for order: 9YDD.130.2J.E4 (DALI) + 3000 + 910600 + 970002 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Ceiling rose



Square ceiling rose
Surface mounted
Recessed

Order code
9717
9714

• To complete this option,
please add ceiling rose colour

Suspension



Suspension type "I" (x4)
Suspension type "Y" (x2)

Order code
910600
910601

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

Order code
K3
K1

• Test function by telecommand signal.

DETAILS




Suspension Type "I"




Suspension Type "Y"

PHOTOMETRY



TML LED 39W DOZ
(640x640mm) 4000K



TML LED 39W DAM
(640x640mm) 4000K

TO SPECIFY:

Suspended architectural LED luminaire, individually mounted. Extruded aluminium body, anodised in natural colour and opal or microprismatic diffuser. Standard version with 4000K, CRI>80 and 65.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, suspension, ceiling rose and 1 or 3 hours emergency unit. - as Roxo Lighting TML LED

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.