



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Industrial areas, commercial areas.

Mounting: Surface/Wall Mounted.

Light Distribution: Direct.

Light Source: LED 4000K, CRI >80, 50.000h life (@L80, B10, Ta 25 C).


Optical System: Diffuser: PMMA.

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt.

PMMA opal diffuser


LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI
	10	1511	148	98	590x48x65	-	-	0,9	902A.111.56.F4	902A.111.56.E4
	21	3022	140	95	1152x48x65	-	-	1,5	902A.122.56.F4	902A.122.56.E4
	26	3777	137	93	1434x48x65	•	•	1,8	902A.127.56.F4	902A.127.56.E4

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code
3000

Connectors



Connector 3-pole mini wieland GST15i3 male. **M3M**
 Connector 5-pole mini wieland GST15i5 DIM male. **M5M**
 Connector 3-pole mini wieland GST15i3 male + 1m cable with 3-pole mini wieland GST15i3 female **M3MFC**
 Connector 5-pole mini wieland GST15i5 DIM male + 1m cable with 5-pole mini wieland GST15i5 DIM female **M5MFC**

Order code

Example code for order: 902A.111.56.E4 (DALI) + 3000 + M5M + K3(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

Emergency unit

Order code



Emergency unit 3 hours
Emergency unit 1 hour

K3
K1

- Test function by telecommand signal.

DETAILS




Side fixture connector on the luminaire




LED detail

PHOTOMETRY



TRN LED 26W
PMMA 4000K



TRN LED 10W
PMMA 4000K

TO SPECIFY:

Surface LED batten with opal PMMA diffuser. Standard version with 4000K, CRI>80 and 50.000h lifetime (@ L80, B10, Ta 25 C). Optional 3000K, DALI dimmable versions, connectors and 1 or 3 hours emergency unit. – as Roxo Lighting TRN LED.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.