

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Offices, Schools, Corridors.

Mounting: Surface/Suspended.

Light Distribution: Direct.


Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt (RAL9016).




RAM - Asymmetric satin aluminium reflector

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x14	595x196x85	3,0	9R2C.114.0C.A4	9R2C.114.0C.84	9R2C.114.0C.74
	1x24	595x196x85	3,0	9R2C.124.0C.A4	9R2C.124.0C.84	9R2C.124.0C.74
	1x28	1195x196x85	3,5	9R2C.128.0C.A4	9R2C.128.0C.84	9R2C.128.0C.74
	1x35	1495x196x85	4,0	9R2C.135.0C.A4	9R2C.135.0C.84	9R2C.135.0C.74
	1x49	1495x196x85	4,0	9R2C.149.0C.A4	9R2C.149.0C.84	9R2C.149.0C.74
	1x54	1195x196x85	3,5	9R2C.154.0C.A4	9R2C.154.0C.84	9R2C.154.0C.74
	1x80	1495x196x85	4,0	9R2C.180.0C.A4	9R2C.180.0C.84	9R2C.180.0C.74


OPTIONS

Code	Description
--	Lamps as optional.

DIMENSIONS



PHOTOMETRY



TO SPECIFY:

Surface asymmetric luminaire individually mounted with satin aluminium reflector. For single fluorescent 14/24/28/35/49/54/80W T5(G5) lamp – as Indelague TSA.

* Lamp not included.
Example code for order: 9R2C.128.0C.74 (DALI)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.