



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Storehouses, Industrial areas, Corridors, Garages, Basements.

Mounting: Surface/Suspended/Wall Mounted.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 65.000h life (@L80, B10, Ta 25 C).


Control Gear: LED driver, 220-240VAC-50/60Hz.

Wiring: Pre-wired 1,5m long H07RN-F cable with plastic cable gland.


Materials: Body: Polycarbonate tube.
End caps: Anodised aluminium.

Surface Finish: White matt powder coated gear tray.

TUP - Transparent polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxB (mm)	K1	K3	kg	HF	DALI
	26	3220	124	100	Ø105x662	-	-	2,9	904N.211.1H.F4	904N.211.1H.E4
	47	6440	137	100	Ø105x1222	-	-	3,2	904N.222.1H.F4	904N.222.1H.E4
	57	8050	140	99	Ø105x1502	•	•	4,5	904N.227.1H.F4	904N.227.1H.E4
	84	13400	152	95	Ø105x1502	-	-	4,5	904N.084.1H.F4	904N.084.1H.E4


TOP - Opal polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxB (mm)	K1	K3	kg	HF	DALI
	26	3220	113	91	Ø105x662	-	-	2,9	904N.211.1G.F4	904N.211.1G.E4
	47	6440	127	93	Ø105x1222	-	-	3,2	904N.222.1G.F4	904N.222.1G.E4
	57	8050	127	90	Ø105x1502	•	•	4,5	904N.227.1G.F4	904N.227.1G.E4
	84	13400	139	87	Ø105x1502	-	-	4,5	904N.084.1G.F4	904N.084.1G.E4

TUP | TOP

• For 84W version LED life time: 48.000h @ L80, B10, Ta 25 C.

DIMENSIONS



Exemple code for order: 904N.227.1H.F4 (HF) + 3000 + 915100 + 910200 + K3 (OPTIONS).

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Stainless steel end caps



IP68 stainless steel end caps (2x)

Order code
276

Fixing system



Stainless steel (x2)
Acrylic (x2)

Order code
915100
915102

Suspension



Suspension type "I" (x2)

• Only for basic stainless steel and plastic fixing holder.

Order code
910200

Emergency unit



Emergency unit 1 hour
Emergency unit 3 hours

• Only available for HF version

Order code
K1
K3

Metal cable gland.



Metal cable gland.

Order code
925000

DETAILS




IP68 Stainless steel end caps with plastic cable gland




IP68 Anodised aluminium end caps with metal cable gland.

PHOTOMETRY



TTM LED 26W
TUP 4000K



TTM LED 26W
TOP 4000K

TO SPECIFY:

Tubular LED luminaire, IP68/IK10, for ceiling surface mounting, ceiling suspension, or wall application. Made in opal or transparent polycarbonate tube, 105mm diameter. In standard with 4000K LED, CRI>80 and 65.000h lifetime (@L80, B10, Ta 25 C), and equipped with HF(on/off) driver. Pre-wired with 1,50mt long H07RN-F cable and with plastic cable gland. Optional dimmable Dali LED driver, and 3000K. Fixing holders, suspensions, metal cable gland, stainless steel end caps and 1 hour or 3 hours Emergency kit available as accessories - as Roxo Lighting TTM LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.