

TTP 70 Colour LED

Downlights



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

| | |
|------------------------------|---|
| Areas of Application: | Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces. |
| Light Source: | LED 4000K, CRI >80, 50.000h life. |
| Control Gear: | LED driver, 220-240VAC-50/60Hz. |
| Wiring: | Pre-wired 1,5m transparent cable with plastic cable gland. |
| Materials: | Body: Polycarbonate tube and injected transparent polycarbonate end caps. |

TOP - Opal polycarbonate diffuser

| LED | W | Lm | Lm/W | η(%) | AxB (mm) | Kg | K1 | HF | DSI | DALI |
|-----|------|------|------|------|----------|-----|----|----------------|----------------|----------------|
| | 1x11 | 1500 | 107 | 87 | Ø72x628 | 1,2 | - | 904P.111.1G.F4 | 904P.111.1G.J4 | 904P.111.1G.E4 |
| | 1x22 | 3000 | 110 | 90 | Ø72x1188 | 1,8 | • | 904P.122.1G.F4 | 904P.122.1G.J4 | 904P.122.1G.E4 |
| | 1x27 | 3750 | 108 | 89 | Ø72x1468 | 2,2 | • | 904P.127.1G.F4 | 904P.127.1G.J4 | 904P.127.1G.E4 |

COLOUR / FINISH

| Code | Description |
|------|-------------|
| B | Black |
| K | Red |
| T | Yellow |
| U | Blue |
| V | Green |
| X | Purple |
| Y | Orange |

OPTIONS


| Code | Description |
|--------|---|
| 3000 | Colour temperature 3000K. |
| 915200 | Basic stainless steel fixing holder (x2). |
| 915202 | Acrylic fixing holder (x2). |
| 910200 | Suspension type "I" (x2) (only for basic stainless steel fixing holder). |
| K1 | Emergency unit 1 hour. |
| -- | IP 44 version. |

DETAILS



Metal cable gland standard for DSI/DALI versions

PHOTOMETRY



DIMENSIONS



TO SPECIFY:

Architectural LED luminaire in opal polycarbonate tube. Luminaire with 72mm diameter, integral LED driver and total luminous flux of 1500/3000/3750lm. Available in surface, suspended or wall mounted versions. Optional colour end caps, IP44 version, dimmable versions and 1 hour emergency available - as Roxo Lighting TTP 70 Colour LED.

Example code for order: 904P.111.1G.E4 (DALI) + B (END CAP COLOURS) + 3000 + 915200 + 910200 (OPTIONS)

We reserve the right to make technical changes without prior notice.