

# TTP 50 360 VRT

## TUBULAR



Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Suspended.

**Light Distribution:** 360°

**Light Source:** LED 4000K, RG0, CRI>80, MacAdam Step <3, 70.000h lifetime (@L80, B10, Ta 25 C).


**Optical System:** Diffuser: Opal polycarbonate.

**Control Gear:** Not included.

**Materials:** Body: Polycarbonate tube  
End caps: Aluminium.




**Surface Finish:** End caps powder coated.

TOP - Opal polycarbonate diffuser


LED	UGR	W	Lm Output	V	L(mm)	kg	Order code
	≤22	10	912	24	570	0,4	90555.L060.0
	≤22	18	1685	24	970	0,65	90555.L090.0
	≤22	23	2275	24	1270	0,7	90555.L120.0
	≤22	29	2916	24	1570	0,83	90555.L150.0
	≤22	34	3370	24	1870	0,98	90555.L180.0
	≤22	37	3744	24	2070	1,3	90555.L200.0

Note:  
• To complete the product add the current supply cable, the ceiling rose and the transformer. Please order it separately.

### END CAP COLOURS

Code	Description
 W	White
 G	Grey
 B	Black

### DIMENSIONS




We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### OPTIONS

#### Colour temperature

Order code



3000K

3000

#### Current supply cable

Order code



Transparent current cable 2 x 0,75mm  
L1500mm  
L3000mm  
L6000mm

942800  
942801  
942802

#### Ceiling Rose

Order code



Ceiling Rose  
Surface mounted T32 D80  
Recessed T31 D90

978801  
978800

• To order this option you must indicate the desired colour

#### 24V Transformer

Order code



24V Transformer  
HF (On-Off)  
DALI

965733  
965734

### DETAILS




End cap with power supply



End cap without power supply

### PHOTOMETRY



TTP 50 360° VRT TOP

#### TO SPECIFY:

Tubular LED luminaire, IP40, for vertical suspended application. Made of Ø50mm opal polycarbonate tube, with inner aluminium profile and aluminium end caps. Available in 6 lengths (570, 970, 1270, 1570, 1870, 2070mm). Standard version with 4000K LED, RG0 (Risk Group 0 for photobiological safety, according to IEC 62471), CRI>80, MacAdam Step<3 and 70.000h lifetime (@ L80, B10, Ta 25 °C). 3000K version, transparent current supply cable, ON-OFF or dimmable DALI driver and recessed ceiling rose (T31 D90) or surface mounted ceiling rose (T32 D80) available as option. - as Roxo Lighting TTP 50 360 VRT.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.