

PHOTOMETRIC RESULTS

Name:	TTP 50 LINE L1460 TOP 830 END LO		
Number:	90484L150-50	Diameter:	0 mm
Report:	07-01-2020	Length:	1460 mm
Meas.-no.:	01	Width:	50 mm
Lamp type:	LED 830 - 01	Height:	50 mm
Number:	1	Power:	28,24 W
Lamp flux:	4300,00 lm	Operator:	INDEL AGUE GROUP
Date:	07-01-2020 12:30:28	Output ratio:	80,8 %

Protocol

LiTG-class: A31
UTE-class: 0,76 G + 0,05 T
IES-class: 43 - 73 - 91 - 94 - 81
TM5-class: BZ5

Divergences in the plane through maximum intensity:	Horizontal	Vertical
One half peak divergence	112,4°	125,1°
Half peak side angle (left)	-56,2°	-62,6°
Half peak side angle (right)	56,2°	62,6°
One tenth peak divergence	160,8°	205,6°
Tenth peak side angle (left)	-80,4°	-102,8°
Tenth peak side angle (right)	80,4°	102,8°


C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						

Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	95,0°
	100,0°	105,0°	110,0°	115,0°	120,0°	125,0°	130,0°	135,0°	140,0°	145,0°
	150,0°	155,0°	160,0°	165,0°	170,0°	175,0°	180,0°			

PHOTOMETRIC RESULTS

Name:	TTP 50 LINE L1460 TOP 830 END LO		
Number:	90484L150-50	Diameter:	0 mm
Report:	07-01-2020	Length:	1460 mm
Meas.-no.:	01	Width:	50 mm
Lamp type:	LED 830 - 01	Height:	50 mm
Number:	1	Power:	28,24 W
Lamp flux:	4300,00 lm	Operator:	INDELAGUE GROUP
Date:	07-01-2020 12:30:28	Output ratio:	80,8 %

Polar diagram TTP 50 LINE L1460 TOP 830 END LO / Total in 15° C / 5° G



PHOTOMETRIC RESULTS

Name:	TTP 50 LINE L1460 TOP 830 END LO		
Number:	90484L150-50	Diameter:	0 mm
Report:	07-01-2020	Length:	1460 mm
Meas.-no.:	01	Width:	50 mm
Lamp type:	LED 830 - 01	Height:	50 mm
Number:	1	Power:	28,24 W
Lamp flux:	4300,00 lm	Operator:	INDEL AGUE GROUP
Date:	07-01-2020 12:30:28	Output ratio:	80,8 %

UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	18,3	19,9	18,8	20,3	20,8	19,2	20,8	19,7	21,2	21,7
2H	3H	20,0	21,4	20,4	21,8	22,3	20,7	22,2	21,2	22,6	23,1
2H	4H	20,7	22,1	21,2	22,5	23,0	21,3	22,7	21,8	23,2	23,7
2H	6H	21,4	22,7	21,9	23,2	23,7	21,8	23,0	22,3	23,5	24,0
2H	8H	21,7	22,9	22,2	23,4	23,9	21,9	23,1	22,4	23,6	24,1
2H	12H	21,9	23,1	22,5	23,6	24,2	21,9	23,1	22,4	23,6	24,1
4H	2H	19,0	20,4	19,5	20,9	21,4	19,7	21,1	20,2	21,5	22,0
4H	3H	20,8	22,0	21,3	22,5	23,0	21,4	22,6	21,9	23,1	23,6
4H	4H	21,8	22,8	22,3	23,3	23,9	22,1	23,2	22,7	23,7	24,3
4H	6H	22,6	23,5	23,1	24,1	24,6	22,6	23,6	23,2	24,1	24,7
4H	8H	23,0	23,8	23,5	24,4	25,0	22,8	23,7	23,3	24,2	24,8
4H	12H	23,3	24,2	23,9	24,7	25,3	22,9	23,7	23,4	24,2	24,9
8H	4H	22,0	22,9	22,6	23,5	24,1	22,4	23,3	22,9	23,8	24,4
8H	6H	23,0	23,8	23,6	24,3	25,0	23,0	23,7	23,5	24,3	24,9
8H	8H	23,6	24,2	24,2	24,9	25,5	23,3	23,9	23,8	24,5	25,1
8H	12H	24,1	24,7	24,7	25,3	25,9	23,4	24,0	24,0	24,6	25,2
12H	4H	22,1	22,9	22,7	23,5	24,1	22,4	23,2	23,0	23,8	24,4
12H	6H	23,2	23,8	23,8	24,4	25,0	23,1	23,8	23,7	24,4	25,0
12H	8H	23,7	24,3	24,3	24,9	25,5	23,4	24,0	24,0	24,6	25,2

UGR values are corrected for lamp flux of 4300 lm by 5,1

PHOTOMETRIC RESULTS

Name:	TTP 50 LINE L1460 TOP 830 END LO		
Number:	90484L150-50	Diameter:	0 mm
Report:	07-01-2020	Length:	1460 mm
Meas.-no.:	01	Width:	50 mm
Lamp type:	LED 830 - 01	Height:	50 mm
Number:	1	Power:	28,24 W
Lamp flux:	4300,00 lm	Operator:	INDEL AGUE GROUP
Date:	07-01-2020 12:30:28	Output ratio:	80,8 %

Luminance [cd/m²] TTP 50 LINE L1460 TOP 830 END LO / Total in 15° C / 5° G

G/C [cd/	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	7134,55	7191,00	7442,10	7942,48	8833,62	10322,0	12833,3	10322,0	8833,62
50,00	6572,01	6617,20	6848,88	7320,81	8196,84	9740,25	12545,0	9740,25	8196,84
55,00	6030,93	6063,50	6261,75	6684,43	7512,08	9095,27	12190,1	9095,27	7512,08
60,00	5505,78	5520,59	5679,42	6034,34	6805,90	8345,70	11748,8	8345,70	6805,90
65,00	4991,35	4986,22	5106,57	5382,17	6020,12	7480,47	11100,6	7480,47	6020,12
70,00	4497,29	4475,40	4543,05	4721,08	5194,95	6425,56	10247,6	6425,56	5194,95
75,00	4020,28	3973,07	3989,55	4060,26	4323,71	5202,38	9005,94	5202,38	4323,71
80,00	3557,65	3499,95	3463,95	3423,04	3465,14	3856,07	7183,04	3856,07	3465,14
85,00	3124,95	3054,56	2969,08	2825,62	2658,71	2493,41	4612,87	2493,41	2658,71

G/C [cd/	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	7942,48	7442,10	7191,00	7134,55	7191,00	7442,10	7942,48	8833,62	10322,0
50,00	7320,81	6848,88	6617,20	6572,01	6617,20	6848,88	7320,81	8196,84	9740,25
55,00	6684,43	6261,75	6063,50	6030,93	6063,50	6261,75	6684,43	7512,08	9095,27
60,00	6034,34	5679,42	5520,59	5505,78	5520,59	5679,42	6034,34	6805,90	8345,70
65,00	5382,17	5106,57	4986,22	4991,35	4986,22	5106,57	5382,17	6020,12	7480,47
70,00	4721,08	4543,05	4475,40	4497,29	4475,40	4543,05	4721,08	5194,95	6425,56
75,00	4060,26	3989,55	3973,07	4020,28	3973,07	3989,55	4060,26	4323,71	5202,38
80,00	3423,04	3463,95	3499,95	3557,65	3499,95	3463,95	3423,04	3465,14	3856,07
85,00	2825,62	2969,08	3054,56	3124,95	3054,56	2969,08	2825,62	2658,71	2493,41

G/C [cd/	270,00	285,00	300,00	315,00	330,00	345,00
45,00	12833,3	10322,0	8833,62	7942,48	7442,10	7191,00
50,00	12545,0	9740,25	8196,84	7320,81	6848,88	6617,20
55,00	12190,1	9095,27	7512,08	6684,43	6261,75	6063,50
60,00	11748,8	8345,70	6805,90	6034,34	5679,42	5520,59
65,00	11100,6	7480,47	6020,12	5382,17	5106,57	4986,22
70,00	10247,6	6425,56	5194,95	4721,08	4543,05	4475,40
75,00	9005,94	5202,38	4323,71	4060,26	3989,55	3973,07
80,00	7183,04	3856,07	3465,14	3423,04	3463,95	3499,95
85,00	4612,87	2493,41	2658,71	2825,62	2969,08	3054,56

HEADQUARTERS

INDÚSTRIA ELÉTRICA DE ÁGUEDA S.A.

Rua da Mina 465 | Covão | Zona industrial EN1 Norte

3750-792 Trofa ÁGUEDA | PORTUGAL

www.indelague.com | www.roxolighting.com

indelague@indelague.pt | roxo.london@roxolighting.com

Tel. (+351) 234 612 310

Fax (+351) 234 624 058