

Norms: EN 60598-1, EN 60598-2-1



IP 20

IP 44

960°C

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface/Suspended/Wall Mounted.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Wiring: Pre-wired 1,5m transparent cable with plastic cable gland.

Materials: Body: Polycarbonate tube.
End caps: Injected transparent polycarbonate.

Surface Finish: Gear tray powder coated in white.

Opal polycarbonate diffuser.

LAMP	W	Lm Output	Lm/W	AxB (mm)	K1	kg	HF	DALI
LED	15	1610	97	Ø72x618	-	1,2	904P.015.1G.F4	904P.015.1G.E4
	26	3220	113	Ø72x1178	•	1,8	904P.026.1G.F4	904P.026.1G.E4

END CAP COLOURS

Code	Description
■ B	Black
■ X	Purple
■ K	Red
■ Y	Orange
■ T	Yellow
■ V	Green
■ U	Blue

DETAILS



Metal cable gland standard for DALI versions

Example code for order: 904P.026.1G.F4 (HF) + 3000 + 915200 + 910200 + K1 (OPTIONS).

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Fixing holders



Stainless steel (x2)

Código
915200

Suspension



Suspension type "I" (x2)

Order code
910200

IP (Ingress protection)



IP44 version
Option supplied under request.

Emergency unit





Emergency unit 1 hour

• Only available for HF version

Order code
K1

PHOTOMETRY

DIMENSIONS



TO SPECIFY:

Tubular LED luminaire, IP20, for ceiling surface, ceiling suspended or wall mounted application. Made in opal polycarbonate tube, Ø72mm diameter and Transparent/Black/Purple/Red/Orange/Yellow/Green/ Blue polycarbonate endcaps. Standard version with 4000K, CRI>80 and 50000h life time (@L80,B10, Ta 25 C). Pre-wired with 1,5m long transparent cable with plastic cable gland. Optional dimmable DALI dimmable driver, 3000K, IP44, fixing holders, suspensions, metal cable gland and 1 hour emergency unit available as optional. - as Roxo Lighting TTP 70 Colour LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.