



Norms: EN 60598-1, EN 60598-2-1



## PRODUCT DESCRIPTION

**Areas of Application:** Storehouses, Industrial areas, Corridors, Garages, Basements.

**Mounting:** Surface/Suspended/Wall Mounted.

**Light Distribution:** Direct.


**Light Source:** T5 (G5) lamp included.

**Control Gear:** Electronic equipment, 220-240VAC-50/60Hz.


**Wiring:** Pre-wired 1,5m long H07RN-F cable with plastic cable gland.

**Materials:** Body: Polycarbonate tube.  
End caps: Injected transparent polycarbonate.

TUP - Transparent polycarbonate diffuser.

	LAMP*	Φ	W	Lm/W	η(%)	AxB (mm)	K1	Kg	HF	DSI	DALI
	T5	G5	1x14	66	92	Ø72x640	-	1	9L4M.114.1H.A4	9L4M.114.1H.84	9L4M.114.1H.74
		G5	1x24	64	91	Ø72x640	-	1	9L4M.124.1H.A4	9L4M.124.1H.84	9L4M.124.1H.74
	G5	1x28	78	92	Ø72x1240	•	1,5	9L4M.128.1H.A4	9L4M.128.1H.84	9L4M.128.1H.74	
	G5	1x35	81	93	Ø72x1540	•	1,9	9L4M.135.1H.A4	9L4M.135.1H.84	9L4M.135.1H.74	
	G5	1x49	77	93	Ø72x1540	•	1,9	9L4M.149.1H.A4	9L4M.149.1H.84	9L4M.149.1H.74	
	G5	1x54	70	90	Ø72x1240	•	1,5	9L4M.154.1H.A4	9L4M.154.1H.84	9L4M.154.1H.74	
	G5	1x80	68	94	Ø72x1540	-	1,9	9L4M.180.1H.A4	9L4M.180.1H.84	9L4M.180.1H.74	

TOP - Opal polycarbonate diffuser.

	LAMP*	Φ	W	Lm/W	η(%)	AxB (mm)	K1	Kg	HF	DSI	DALI
	T5	G5	1x14	62	86	Ø72x640	-	1	9L4M.114.1G.A4	9L4M.114.1G.84	9L4M.114.1G.74
		G5	1x24	59	84	Ø72x640	-	1	9L4M.124.1G.A4	9L4M.124.1G.84	9L4M.124.1G.74
	G5	1x28	74	87	Ø72x1240	•	1,5	9L4M.128.1G.A4	9L4M.128.1G.84	9L4M.128.1G.74	
	G5	1x35	76	87	Ø72x1540	•	1,9	9L4M.135.1G.A4	9L4M.135.1G.84	9L4M.135.1G.74	
	G5	1x49	72	87	Ø72x1540	•	1,9	9L4M.149.1G.A4	9L4M.149.1G.84	9L4M.149.1G.74	
	G5	1x54	66	84	Ø72x1240	•	1,5	9L4M.154.1G.A4	9L4M.154.1G.84	9L4M.154.1G.74	
	G 5	1x80	63	88	Ø72x1540	-	1,9	9L4M.180.1G.A4	9L4M.180.1G.84	9L4M.180.1G.74	

Please note: 1x80W only to be used in low temperature applications. Ambient temperature must be under 15 °C.

\* Lamp included


Example code for order: 9L4M.154.1H.74 (DALI) + 915200 + 910200 + 925000 + 940201 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## OPTIONS

Code	Description
915200	Basic stainless steel fixing holder (x2).
915202	Acrylic fixing holder (x2).
910200	Suspension type "I" (x2) (Only for basic stainless steel and plastic fixing holder).
K1	Emergency unit 1 hour.
925000	Metal cable gland.
940200	1,5m current cable 2x1,5mm <sup>2</sup> for indoor applications.
940201	1,5m current cable 4x1,5mm <sup>2</sup> for indoor applications.

## DIMENSIONS



## DETAILS




Basic stainless steel fixing holder



Acrylic fixing holder

## PHOTOMETRY



### TO SPECIFY:

Waterproof luminaire IP68 in transparent/opal polycarbonate tube.  
Luminaire with 72mm diameter, available with single □  
14/24/28/35/49/54/80W T5(G5) fluorescent lamp. Optional surface,  
suspended or wall mounted versions, dimmable versions and 1 hour  
emergency available - as Indelague TTP 70.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.