



**LED**

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Storehouses, Industrial areas, Corridors, Garages, Basements.

**Mounting:** Surface/Suspended/Wall Mounted.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 65.000h life (@L80, B10, Ta 25 C).


**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Wiring:** Pre-wired 1,5m long H07RN-F cable with plastic cable gland.


**Materials:** Body: Polycarbonate tube.  
End caps: Injected transparent polycarbonate.

**Surface Finish:** White matt powder coated gear tray.


TUP - Transparent polycarbonate diffuser.

LED	W	Lm	Lm/W	η(%)	AxB (mm)	K1	kg	HF	DALI
	15	1610	105	100	Ø52x620	-	0,9	907E.015.1H.F4	907E.015.1H.E4
	26	3220	124	100	Ø52x1180	•	1,3	907E.026.1H.F4	907E.026.1H.E4
	31	4025	131	100	Ø52x1460	•	1,5	907E.031.1H.F4	907E.031.1H.E4

TOP - Opal polycarbonate diffuser.

LED	W	Lm	Lm/W	η(%)	AxB (mm)	K1	kg	HF	DALI
	15	1610	96	89	Ø52x620	-	0,9	907E.015.1G.F4	907E.015.1G.E4
	26	3220	113	91	Ø52x1180	•	1,3	907E.026.1G.F4	907E.026.1G.E4
	31	4025	118	91	Ø52x1460	•	1,5	907E.031.1G.F4	907E.031.1G.E4

**DIMENSIONS**



Exemple code for order: 907E.031.1G.F4 (HF) + 3000 + 915003 + 910200 + K1 (OPTIONS).

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## OPTIONS


### Colour temperature



3000K

Order code  
**3000**

### Fixing holders



Standard stainless steel (x2)  
Stainless steel (x2)  
Plastic (x2)  
Acrylic (x2)

Order code  
**915003**  
**915000**  
**915001**  
**915002**

### Suspension type "I"



Suspension type "I" (x2)

• Only for standard stainless steel fixing holder.

Order code  
**910200**

### Emergency unit



Emergency unit 1 hour

• Only available for HF version

Order code  
**K1**


### Metal cable gland.




Metal cable gland.

Order code  
**925000**

## PHOTOMETRY



**TTP LED 15W  
TUP 4000K**



**TTP LED 15W  
TOP 4000K**

### TO SPECIFY:

Tubular LED luminaire, IP68/IK10, for ceiling surface mounting, ceiling suspension, or wall application. Made in opal or transparent polycarbonate tube, 52mm diameter. In standard with 4000K LED, CRI>80 and 65.000h lifetime (@L80, B10, Ta 25 C), and equipped with HF(on/off) driver. Pre-wired with 1,50mt long H07RN-F cable and with plastic cable gland. Optional dimmable DALI driver, 3000K, fixing system, suspensions, metal cable gland and 1 hour emergency unit.- as Roxo Lighting TTP LED.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.