



LED



Norms: EN 60598-1, EN 60598-2-1

CE IP 20

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Light Distribution: Direct.

Light Source: LED 3000K, CRI>80, 50.000h life.

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Wiring: 1,5m long cable H05VV-F.

Materials: Body: Aluminium.

Surface Finish: Powder coated.

DOZ - Opal polycarbonate diffuser

LED	W	Lm	AxB (mm)	Kg	ORDER CODE
	1	101	Ø136x60	0,5	90231.L101.E
	3	187	Ø136x60	0,5	90231.L103.E

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)
U	Blue (RAL 5002)
K	Red (RAL 3020)
V	Green (RAL 6018)
T	Yellow (RAL 1021)

OPTIONS

Code	Description
5700	Colour temperature 5700K.

DETAILS





Ceiling rose detail

Example code for order: 90231.L101.E (ORDER CODE) + W (COLOUR/FINISH) + 5700 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

DIMENSIONS



TO SPECIFY:

Suspended LED architectural spot. Optional 5700K, white, grey, black, red, yellow, green or blue finish - as Roxo Lighting UFO.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.