



**LED**

Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

**Mounting:** Surface.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>90, MacAdam Step<3, 64.000h life (@L80, B10, Ta 25 C).

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium tube.

**Surface Finish:** Powder coated.


### LIGHT+ - Opal diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
	≤22	8	780	65	67	Ø95x206	1,2	90447.L008.E	-
	≤22	10	1100	70	64	Ø95x206	1,2	90447.L011.E	90447.L011.H
	≤25	13	1540	76	64	Ø95x206	1,2	90447.L015.E	90447.L015.H

### COLOUR / FINISH


Code	Description
□ W	White
■ B	Black
■ G	Grey

### DIMENSIONS



### OPTIONS

#### Colour temperature




3000K

Order code  
**3000**

Example code for order: 90447.L015.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**PHOTOMETRY**



**VEGA IP Ø95 LIGHT+**  
**4000K HO**

**TO SPECIFY:**

Circular LED downlight, with Ø95mm and IP54 for surface application. Extruded aluminium body, powder coated in epoxy-polyester in white, grey and black. With three possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 64.000h lifetime (@L80, B10, Ta 25 C). Optional DALI dimmable LED driver and 3000K. - as Indelague VEGA IP.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.