



**LED**

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

**Mounting:** Surface/Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>90, MacAdam Step<3, 64.000h life (@L80, B10, Ta 25 C).

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium tube.

**Surface Finish:** Powder coated.

**LIGHT+ - Opal diffuser**

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
	≤22	8	780	65	67	Ø95x200	1,2	90443.L008.E	-
	≤22	10	1100	70	64	Ø95x200	1,2	90443.L011.E	90443.L011.H
	≤25	13	1540	76	64	Ø95x200	1,2	90443.L015.E	90443.L015.H




**PRISM+ - Microprismatic diffuser**

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
	≤19	8	780	64	66	Ø95x200	1,2	90445.L008.E	-
	≤19	10	1100	70	64	Ø95x200	1,2	90445.L011.E	90445.L011.H
	≤19	13	1540	76	64	Ø95x200	1,2	90445.L015.E	90445.L015.H

**COLOUR / FINISH**

Code	Description
W	White
B	Black
G	Grey

**DIMENSIONS**



Example code for order: 90443.L015.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**


**Colour temperature**



3000K

Order code  
**3000**

**Suspension kit**



Recessed ceiling rose  
HF  
DALI


Order code  
**912620**  
**912630**

Surface ceiling rose  
HF  
DALI


**912600**  
**912610**

- Transparent current supply cable included.
- To complete this option, please add ceiling rose colour.

**PHOTOMETRY**



**VEGA D95 LIGHT+**  
4000K HO



**VEGA D95 PRISM+**  
4000K HO

**TO SPECIFY:**

Circular LED downlight, with Ø95 mm for surface or suspended application. Available with plain opal diffuser LIGHT+ or microprismatic diffuser PRISM+ (allows a high visual comfort (UGR<19) according to EN 12464-1). Extruded aluminium body, powder coated in epoxy-polyester in white, grey and black. With three possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 64.000h lifetime (@L80, B10, Ta 25 C). Optional DALI dimmable LED driver, 3000K, suspension kit and surface or recessed ceiling rose. - as Indelague VEGA.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.