

## PHOTOMETRIC RESULTS

<b>Name:</b>	WEBB /E 2 L280W140 PB 940 35° HO		
<b>Number:</b>	90656L002	<b>Diameter:</b>	0 mm
<b>Report:</b>	04-01-2021	<b>Length:</b>	140 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	140 mm
<b>Lamp type:</b>	LED 940 - 01	<b>Height:</b>	98 mm
<b>Number:</b>	1	<b>Power:</b>	14,21 W
<b>Lamp flux:</b>	1809,00 lm	<b>Operator:</b>	INDELAGUE GROUP
<b>Date:</b>	04/01/2022 11:51:22	<b>Output ratio:</b>	86,8 %


## Info

LiTG-class:	A60										
UTE-class:	Not available										
IES-class:	98 - 100 - 100 - 100 - 86										
TM5-class:	BZ1										
Divergences in the plane through maximum intensity:						Horizontal		Vertical			
One half peak divergence:						27,3°		27,1°			
Half peak side angle (left):						-14,1°		-14,1°			
Half peak side angle (right):						13,1°		13,0°			
One tenth peak divergence:						73,1°		73,2°			
Tenth peak side angle (left):						-37,0°		-37,2°			
Tenth peak side angle (right):						36,0°		36,0°			
C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°	
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°	
	300,0°	315,0°	330,0°	345,0°							
Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°	
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°		

## PHOTOMETRIC RESULTS

Name:	WEBB /E 2 L280W140 PB 940 35° HO		
Number:	90656L002	Diameter:	0 mm
Report:	04-01-2021	Length:	140 mm
Meas.-no.:	01	Width:	140 mm
Lamp type:	LED 940 - 01	Height:	98 mm
Number:	1	Power:	14,21 W
Lamp flux:	1809,00 lm	Operator:	INDELAGUE GROUP
Date:	04/01/2022 11:51:22	Output ratio:	86,8 %

Polar diagram WEBB /E 2 L280W140 PB 940 35° HO / Direct in 15° C / 5° G



## PHOTOMETRIC RESULTS

<b>Name:</b>	WEBB /E 2 L280W140 PB 940 35° HO		
<b>Number:</b>	90656L002	<b>Diameter:</b>	0 mm
<b>Report:</b>	04-01-2021	<b>Length:</b>	140 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	140 mm
<b>Lamp type:</b>	LED 940 - 01	<b>Height:</b>	98 mm
<b>Number:</b>	1	<b>Power:</b>	14,21 W
<b>Lamp flux:</b>	1809,00 lm	<b>Operator:</b>	INDELAGUE GROUP
<b>Date:</b>	04/01/2022 11:51:22	<b>Output ratio:</b>	86,8 %

## UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	19,8	20,7	20,2	21,0	21,3	19,8	20,6	20,1	20,9	21,3
2H	3H	19,6	20,3	20,0	20,7	21,0	19,5	20,3	19,9	20,6	21,0
2H	4H	19,5	20,2	19,9	20,5	20,9	19,4	20,1	19,8	20,5	20,9
2H	6H	19,4	20,0	19,8	20,4	20,8	19,3	20,0	19,7	20,3	20,7
2H	8H	19,3	19,9	19,7	20,3	20,7	19,2	19,9	19,7	20,2	20,7
2H	12H	19,2	19,8	19,6	20,2	20,6	19,2	19,8	19,6	20,1	20,6
4H	2H	19,5	20,2	19,9	20,5	20,9	19,4	20,1	19,8	20,5	20,9
4H	3H	19,2	19,8	19,6	20,2	20,6	19,2	19,7	19,6	20,1	20,6
4H	4H	19,1	19,6	19,6	20,0	20,5	19,1	19,6	19,5	20,0	20,4
4H	6H	19,0	19,4	19,4	19,9	20,3	18,9	19,4	19,4	19,8	20,3
4H	8H	18,9	19,3	19,4	19,8	20,2	18,8	19,3	19,3	19,7	20,2
4H	12H	18,8	19,2	19,3	19,7	20,2	18,8	19,2	19,3	19,6	20,1
8H	4H	18,9	19,3	19,4	19,8	20,2	18,8	19,2	19,3	19,7	20,2
8H	6H	18,7	19,1	19,2	19,5	20,0	18,7	19,0	19,2	19,5	20,0
8H	8H	18,7	19,0	19,2	19,5	20,0	18,6	18,9	19,2	19,5	20,0
8H	12H	18,6	18,8	19,2	19,4	19,9	18,6	18,8	19,1	19,3	19,8
12H	4H	18,8	19,2	19,3	19,7	20,2	18,8	19,2	19,3	19,6	20,1
12H	6H	18,7	19,0	19,2	19,5	20,0	18,6	18,9	19,2	19,5	19,9
12H	8H	18,6	18,8	19,1	19,4	19,9	18,6	18,8	19,1	19,3	19,8

UGR values are corrected for lamp flux of 1809 lm by 2,1

## PHOTOMETRIC RESULTS

<b>Name:</b>	WEBB /E 2 L280W140 PB 940 35° HO		
<b>Number:</b>	90656L002	<b>Diameter:</b>	0 mm
<b>Report:</b>	04-01-2021	<b>Length:</b>	140 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	140 mm
<b>Lamp type:</b>	LED 940 - 01	<b>Height:</b>	98 mm
<b>Number:</b>	1	<b>Power:</b>	14,21 W
<b>Lamp flux:</b>	1809,00 lm	<b>Operator:</b>	INDEL AGUE GROUP
<b>Date:</b>	04/01/2022 11:51:22	<b>Output ratio:</b>	86,8 %

Luminance [cd/m<sup>2</sup>] WEBB /E 2 L280W140 PB 940 35° HO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	6693,38	6584,80	6695,98	6707,16	6790,62	6379,17	6334,58	6379,17	6790,62
50,00	1495,64	1563,75	1506,88	1684,15	1447,31	1449,63	1393,69	1449,63	1447,31
55,00	773,59	714,02	845,31	911,36	843,96	779,96	911,08	779,96	843,96
60,00	443,71	446,95	448,40	523,23	372,62	447,37	447,92	447,37	372,62
65,00	349,97	352,52	352,80	353,40	352,29	352,86	353,29	352,86	352,29
70,00	432,44	435,59	435,94	436,68	435,31	436,01	436,55	436,01	435,31
75,00	571,46	575,62	576,08	577,05	575,24	576,17	576,88	576,17	575,24
80,00	851,75	857,95	858,64	860,08	857,38	858,77	859,83	858,77	857,38
85,00	1697,01	1709,38	1710,74	1713,62	1708,24	1711,00	1713,11	1711,00	1708,24

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	6707,16	6695,98	6584,80	6693,38	6584,80	6695,98	6707,16	6790,62	6379,17
50,00	1684,15	1506,88	1563,75	1495,64	1563,75	1506,88	1684,15	1447,31	1449,63
55,00	911,36	845,31	714,02	773,59	714,02	845,31	911,36	843,96	779,96
60,00	523,23	448,40	446,95	443,71	446,95	448,40	523,23	372,62	447,37
65,00	353,40	352,80	352,52	349,97	352,52	352,80	353,40	352,29	352,86
70,00	436,68	435,94	435,59	432,44	435,59	435,94	436,68	435,31	436,01
75,00	577,05	576,08	575,62	571,46	575,62	576,08	577,05	575,24	576,17
80,00	860,08	858,64	857,95	851,75	857,95	858,64	860,08	857,38	858,77
85,00	1713,62	1710,74	1709,38	1697,01	1709,38	1710,74	1713,62	1708,24	1711,00

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	6334,58	6379,17	6790,62	6707,16	6695,98	6584,80
50,00	1393,69	1449,63	1447,31	1684,15	1506,88	1563,75
55,00	911,08	779,96	843,96	911,36	845,31	714,02
60,00	447,92	447,37	372,62	523,23	448,40	446,95
65,00	353,29	352,86	352,29	353,40	352,80	352,52
70,00	436,55	436,01	435,31	436,68	435,94	435,59
75,00	576,88	576,17	575,24	577,05	576,08	575,62
80,00	859,83	858,77	857,38	860,08	858,64	857,95
85,00	1713,11	1711,00	1708,24	1713,62	1710,74	1709,38