



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet and extruded aluminium tube.

Surface Finish: Powder coated epoxy polyester.

PB - Polished aluminium reflector | 35° Beam angle



UGR	W	Lm	Lm/W	Kg	HF	DALI
≤19	20	2322	116	1,4	90647.L002.E.0035	90647.L002.H.0035
≤22	28	3148	112	1,4	90659.L002.E.0035	90659.L002.H.0035

PB - Polished reflector - 60°




UGR	W	Lm	Lm/W	Kg	HF	DALI
≤22	20	2322	116	1,4	90647.L002.E.0060	90647.L002.H.0060
≤25	28	3148	112	1,4	90659.L002.E.0060	90659.L002.H.0060

COLOUR / FINISH

Code	Description
□ W	White
■ G	Grey
■ B	Black

DETAILS



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code

3000

Safety cable




Steel safety cable


Order code

955010


PHOTOMETRY




WEBB Spot/E 2 PB
4000K 35° HO



WEBB Spot/E 2 PB
4000K 35° LO




WEBB Spot/E 2 PB
4000K 60° HO



WEBB Spot/E 2 PB
4000K 60° LO

DIMENSIONS



TO SPECIFY:

LED luminaire, with two Ø80mm spotlights, 190° rotatable and ±105° tiltable, for recessed application. Possibility of 35° and 60° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 3148Lm in HO version and 2700Lm in LO version. LED with 116Lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 65.000h lifetime (@L90, B10, Ta 25 °C). DALI dimming and 3000K available as options. - as Roxo Lighting WEBB SPOT /E 2

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.