



LED

Norms: EN 60598-1, EN 60598-2-1



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Track system.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz and track adapter.

Materials: Body: Steel sheet and extruded aluminium tube.

Surface Finish: Powder coated epoxy polyester.

PB - Polished aluminium reflector | 35° Beam angle



UGR	W	Lm	Lm/W	Kg	HF	DALI
≤19	11	1161	106	0,5	90645.L001.E.0035	90645.L001.H.0035
≤22	15	1574	105	0,5	90658.L001.E.0035	90658.L001.H.0035

PB - Polished reflector - 60°



UGR	W	Lm	Lm/W	Kg	HF	DALI
≤22	11	1161	106	0,5	90645.L001.E.0060	90645.L001.H.0060
≤25	15	1574	105	0,5	90658.L001.E.0060	90658.L001.H.0060

COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black

DETAILS




Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature


Order code




3000K

3000


PHOTOMETRY




WEBB Spot Track PB
4000K 35° HO



WEBB Spot Track PB
4000K 35° LO



WEBB Spot Track PB
4000K 60° HO



WEBB Spot Track PB
4000K 60° LO

DIMENSIONS



TO SPECIFY:

LED luminaire, with Ø80mm spotlight, 350° rotatable and 105° tiltable, to be applied in 3-phase track system. Possibility of 35° and 60° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 1574Lm in HO version and 1161Lm in LO version. LED with 116Lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 65.000h lifetime (@L90, B10, Ta 25 °C). DALI dimming and 3000K available as options. - as Indelague WEBB SPOT TRACK

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.