

PHOTOMETRIC RESULTS

Name:	WEBB SQ /C 2 L285W145 PB 930 35° LO		
Number:	90565L002	Diameter:	0 mm
Report:	13-10-2021	Length:	142,5 mm
Meas.-no.:	01	Width:	145 mm
Lamp type:	LED 930 - 01	Height:	140 mm
Number:	1	Power:	10,03 W
Lamp flux:	1249,00 lm	Operator:	INDELAGUE GROUP
Date:	03/11/2021 12:42:50	Output ratio:	85,0 %


Info

LiTG-class:	A60									
UTE-class:	Not available									
IES-class:	97 - 100 - 100 - 100 - 85									
TM5-class:	BZ1									
Divergences in the plane through maximum intensity:						Horizontal		Vertical		
One half peak divergence:						27,2°		27,0°		
Half peak side angle (left):						-12,9°		-12,8°		
Half peak side angle (right):						14,3°		14,2°		
One tenth peak divergence:						73,3°		73,5°		
Tenth peak side angle (left):						-35,9°		-36,3°		
Tenth peak side angle (right):						37,4°		37,2°		
C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						
Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	

PHOTOMETRIC RESULTS

Name:	WEBB SQ /C 2 L285W145 PB 930 35° LO		
Number:	90565L002	Diameter:	0 mm
Report:	13-10-2021	Length:	142,5 mm
Meas.-no.:	01	Width:	145 mm
Lamp type:	LED 930 - 01	Height:	140 mm
Number:	1	Power:	10,03 W
Lamp flux:	1249,00 lm	Operator:	INDELAGUE GROUP
Date:	03/11/2021 12:42:50	Output ratio:	85,0 %

Polar diagram WEBB SQ /C 2 L285W145 PB 930 35° LO / Direct in 15° C / 5° G



PHOTOMETRIC RESULTS

Name:	WEBB SQ /C 2 L285W145 PB 930 35° LO			
Number:	90565L002	Diameter:	0 mm	
Report:	13-10-2021	Length:	142,5 mm	
Meas.-no.:	01	Width:	145 mm	
Lamp type:	LED 930 - 01	Height:	140 mm	
Number:	1	Power:	10,03 W	
Lamp flux:	1249,00 lm	Operator:	INDELAGUE GROUP	
Date:	03/11/2021 12:42:50	Output ratio:	85,0 %	

UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	18,5	19,4	18,9	19,7	20,0	18,5	19,4	18,9	19,7	20,0
2H	3H	18,3	19,1	18,7	19,4	19,8	18,3	19,0	18,7	19,4	19,7
2H	4H	18,2	18,9	18,6	19,3	19,6	18,2	18,9	18,6	19,2	19,6
2H	6H	18,1	18,8	18,5	19,1	19,5	18,1	18,7	18,5	19,1	19,5
2H	8H	18,0	18,7	18,4	19,0	19,4	18,0	18,6	18,4	19,0	19,4
2H	12H	18,0	18,5	18,4	18,9	19,4	17,9	18,5	18,3	18,9	19,3
4H	2H	18,2	18,9	18,6	19,3	19,6	18,2	18,9	18,6	19,2	19,6
4H	3H	17,9	18,5	18,4	18,9	19,4	17,9	18,5	18,3	18,9	19,3
4H	4H	17,9	18,4	18,3	18,8	19,2	17,8	18,3	18,2	18,7	19,2
4H	6H	17,7	18,2	18,2	18,6	19,1	17,6	18,1	18,1	18,6	19,0
4H	8H	17,6	18,1	18,1	18,5	19,0	17,6	18,0	18,1	18,5	18,9
4H	12H	17,6	18,0	18,1	18,4	19,0	17,5	17,9	18,0	18,4	18,9
8H	4H	17,6	18,0	18,1	18,5	19,0	17,6	18,0	18,1	18,5	18,9
8H	6H	17,4	17,8	18,0	18,3	18,8	17,4	17,8	17,9	18,2	18,7
8H	8H	17,4	17,7	18,0	18,3	18,8	17,4	17,7	17,9	18,2	18,7
8H	12H	17,4	17,6	17,9	18,1	18,7	17,3	17,6	17,9	18,1	18,6
12H	4H	17,6	18,0	18,1	18,4	18,9	17,5	17,9	18,0	18,4	18,9
12H	6H	17,4	17,7	18,0	18,2	18,7	17,4	17,7	17,9	18,2	18,7
12H	8H	17,4	17,6	17,9	18,1	18,6	17,3	17,5	17,8	18,1	18,6

UGR values are corrected for lamp flux of 1249 lm by 0,8

PHOTOMETRIC RESULTS

Name:	WEBB SQ /C 2 L285W145 PB 930 35° LO		
Number:	90565L002	Diameter:	0 mm
Report:	13-10-2021	Length:	142,5 mm
Meas.-no.:	01	Width:	145 mm
Lamp type:	LED 930 - 01	Height:	140 mm
Number:	1	Power:	10,03 W
Lamp flux:	1249,00 lm	Operator:	INDEL AGUE GROUP
Date:	03/11/2021 12:42:50	Output ratio:	85,0 %

Luminance [cd/m²] WEBB SQ /C 2 L285W145 PB 930 35° LO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	6275,04	6235,00	6188,68	6177,98	6403,55	6543,85	6700,08	6543,85	6403,55
50,00	1610,69	1498,64	1500,14	1497,63	1616,87	1612,54	1612,30	1612,54	1616,87
55,00	773,59	839,83	840,69	839,17	905,92	903,54	903,42	903,54	905,92
60,00	591,62	518,59	445,05	444,27	445,38	444,21	444,16	444,21	445,38
65,00	349,97	350,67	351,03	350,41	351,29	350,37	350,32	350,37	351,29
70,00	432,44	433,31	433,75	432,98	434,07	432,93	432,88	432,93	434,07
75,00	571,46	429,24	429,63	572,17	430,06	429,02	572,03	429,02	430,06
80,00	851,75	853,46	640,36	639,40	641,00	639,45	852,60	639,45	641,00
85,00	1697,01	1700,42	1275,85	1699,14	1277,12	1274,03	1698,71	1274,03	1277,12

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	6177,98	6188,68	6235,00	6275,04	6235,00	6188,68	6177,98	6403,55	6543,85
50,00	1497,63	1500,14	1498,64	1610,69	1498,64	1500,14	1497,63	1616,87	1612,54
55,00	839,17	840,69	839,83	773,59	839,83	840,69	839,17	905,92	903,54
60,00	444,27	445,05	518,59	591,62	518,59	445,05	444,27	445,38	444,21
65,00	350,41	351,03	350,67	349,97	350,67	351,03	350,41	351,29	350,37
70,00	432,98	433,75	433,31	432,44	433,31	433,75	432,98	434,07	432,93
75,00	572,17	429,63	429,24	571,46	429,24	429,63	572,17	430,06	429,02
80,00	639,40	640,36	853,46	851,75	853,46	640,36	639,40	641,00	639,45
85,00	1699,14	1275,85	1700,42	1697,01	1700,42	1275,85	1699,14	1277,12	1274,03

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	6700,08	6543,85	6403,55	6177,98	6188,68	6235,00
50,00	1612,30	1612,54	1616,87	1497,63	1500,14	1498,64
55,00	903,42	903,54	905,92	839,17	840,69	839,83
60,00	444,16	444,21	445,38	444,27	445,05	518,59
65,00	350,32	350,37	351,29	350,41	351,03	350,67
70,00	432,88	432,93	434,07	432,98	433,75	433,31
75,00	572,03	429,02	430,06	572,17	429,63	429,24
80,00	852,60	639,45	641,00	639,40	640,36	853,46
85,00	1698,71	1274,03	1277,12	1699,14	1275,85	1700,42