



**LED**

Norms: EN 60598-1, EN 60598-2-1



230V/50Hz

**PRODUCT DESCRIPTION**

**Areas of Application:** Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Surface.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step <3, 65.000h life (@L90, B10, Ta 25 C).


**Optical System:** Reflector: Polished aluminium.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.


**Materials:** Body: Steel sheet and extruded aluminium tube.

**Surface Finish:** Powder coated epoxy polyester.

PB - Polished aluminium reflector | 35° Beam angle

	UGR	W	Lm	Lm/W	Kg	HF	DALI
	≤19	10	1161	116	1,6	90565.L001.E.0035	90565.L001.H.0035
	≤22	14	1574	112	1,6	90652.L001.E.0035	90652.L001.H.0035


PB - Polished reflector - 60°

	UGR	W	Lm	Lm/W	Kg	HF	DALI
	≤22	10	1161	116	1,6	90565.L001.E.0060	90565.L001.H.0060
	≤25	14	1574	112	1,6	90652.L001.E.0060	90652.L001.H.0060

**COLOUR / FINISH**

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input checked="" type="checkbox"/> B	Black

**DETAILS**



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**

Colour temperature


Order code




3000K

**3000**


**PHOTOMETRY**




**WEBB Sq /C 1 PB**  
4000K 35° HO



**WEBB Sq /C 1 PB**  
4000K 35° LO




**WEBB Sq /C 1 PB**  
4000K 60° HO



**WEBB Sq /C 1 PB**  
4000K 60° LO

**DIMENSIONS**



**TO SPECIFY:**

Square LED luminaire, 145x145mm, with adjustable downlight for surface mounted application. Possibility of 35° and 60° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 1574Lm in HO version and 1161Lm in LO version. LED with 116Lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 65.000h lifetime (@L90, B10, Ta 25 C). DALI dimming and 3000K available as options. - as Roxo Lighting WEBB /C 1