



Norms: EN 60598-1, EN 60598-2-1



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet and extruded aluminium tube.

Surface Finish: Powder coated epoxy polyester.

PB - Polished aluminium reflector | 35° Beam angle




| UGR | W | Lm | Lm/W | Kg | HF | DALI |
|-----|----|------|------|-----|-------------------|-------------------|
| ≤19 | 20 | 2322 | 116 | 2,6 | 90565.L002.E.0035 | 90565.L002.H.0035 |
| ≤22 | 28 | 3148 | 112 | 2,6 | 90652.L002.E.0035 | 90652.L002.H.0035 |

PB - Polished reflector - 60°



| UGR | W | Lm | Lm/W | Kg | HF | DALI |
|-----|----|------|------|-----|-------------------|-------------------|
| ≤22 | 20 | 2322 | 116 | 2,6 | 90565.L002.E.0060 | 90565.L002.H.0060 |
| ≤25 | 28 | 3148 | 112 | 2,6 | 90652.L002.E.0060 | 90652.L002.H.0060 |

DETAILS



Front view

TO SPECIFY:

Square LED luminaire, 145x145mm, with two adjustable downlights for surface mounted application. Possibility of 35° and 60° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 3148Lm in HO version and 2700Lm in LO version. LED with 116Lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 65.000h lifetime (@L90, B10, Ta 25 C). DALI dimming and 3000K available as options. - as Roxo Lighting WEBB /C 2

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.