



LED

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step <3, 65.000h life (@L90, B10, Ta 25 C).

**Optical System:** Reflector: Polished aluminium.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet and extruded aluminium tube.

**Surface Finish:** Powder coated epoxy polyester.

PB - Polished aluminium reflector | 35° Beam angle

	UGR	W	Lm	Lm/W	Kg	HF	DALI
	≤19	20	2322	116	1,3	90597.L002.E.0035	90597.L002.H.0035
	≤22	28	3148	112	1,3	90657.L002.E.0035	90657.L002.H.0035


PB - Polished reflector - 60°

	UGR	W	Lm	Lm/W	Kg	HF	DALI
	≤22	20	2322	116	1,3	90597.L002.E.0060	90597.L002.H.0060
	≤25	28	3148	112	1,3	90657.L002.E.0060	90657.L002.H.0060

**COLOUR / FINISH**

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

**DETAILS**



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**

**Colour temperature**

Order code

**Safety cable**

Order code



3000K


3000




Steel safety cable

955010


**PHOTOMETRY**




**WEBB Sq /E 2 PB**  
4000K 35° HO



**WEBB Sq /E 2 PB**  
4000K 35° LO




**WEBB Sq /E 2 PB**  
4000K 60° HO



**WEBB Sq /E 2 PB**  
4000K 60° LO

**DIMENSIONS**



**TO SPECIFY:**

Rectangular LED luminaire, 280x140mm, with two adjustable downlights for recessed application. Possibility of 35 and 60 reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 3148Lm in HO version and 2700Lm in LO version. LED with 116Lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 65.000h lifetime (@L90, B10, Ta 25 C). DALI dimming and 3000K available as options. - as Indelague WEBB SQ /E 2

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.