

LED



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.

Fixing system: Brackets.

DOZ - Opal polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	LED	K1	K3	Kg	HF	DALI
	1x30	4080	65	53	890x72x81	880x60	-	-	2,2	90053.L130.E	90053.L130.H
	1x40	5440	64	52	1175x72x81	1165x60	•	•	2,9	90053.L140.E	90053.L140.H
	1x50	6800	63	51	1460x72x81	1450x60	•	•	3,6	90053.L150.E	90053.L150.H
	1x60	8160	65	53	1745x72x81	1735x60	•	•	4,4	90053.L160.E	90053.L160.H
	1x70	9520	65	53	2030x72x81	2020x60	•	•	5,1	90053.L170.E	90053.L170.H
	1x80	10880	63	52	2315x72x81	2305x60	•	•	5,8	90053.L180.E	90053.L180.H
	1x90	12240	64	52	2600x72x81	2590x60	•	•	6,5	90053.L190.E	90053.L190.H
	1x100	13600	63	51	2885x72x81	2875x60	•	•	7,2	90053.L100.E	90053.L100.H

COLOUR / FINISH


Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

OPTIONS

Colour temperature

	3000K	Order code 3000
--	-------	---------------------------



Emergency unit

	Emergency unit 3 hours Emergency unit 1 hour	Order code K3 K1
---	---	--------------------------------------

Example code for order: 90053.L150.H (DALI) + 3000 (OPTIONS).

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY




PERFORMANCE

WIND LED D0Z

LED: 1 x 40W
SPACING: 79m x 1,2m
CEILING HEIGHT: 3m
MAINTENANCE: 0,8
REFLECTANCE: 70/50/20
WORKING PLACE: 0,0m
ILLUMINANCE: 137 lux



DIMENSIONS



TO SPECIFY:

Linear recessed LED luminaire, individually mounted with 72mm width extruded aluminium profile, anodised in natural colour with opal polycarbonate diffuser. Available with HF or DALI control gear. Optional 3000K and 1 or 3 hours emergency – as Indelague WIND LED.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.