



LED

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Police stations, detention centres, public spaces, psychiatric hospitals, schools.

**Mounting:** Ceiling/Wall Surface.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).


**Optical System:** Diffuser: 3mm polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.


**Materials:** Body: Steel sheet.  
Frame: Steel sheet.

**Surface Finish:** White matt powder coated.

DOZ - Opal polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	42	6000	86	60	1215x175x175	11	906I.222.2J.F4	906I.222.2J.E4
	52	7500	88	61	1515x175x175	13	906I.227.2J.F4	906I.227.2J.E4


**DETAILS**



Tamper proof screws

**OPTIONS**

**Special coating**



Anti-Graffiti  
Anti-Sticker

Order code  
**under request**  
**under request**

**Colour temperature**




3000K  
Tunable white

Order code  
**3000**  
**T000**

Example code for order: 906J.227.2J.F4 (HF) + 3000 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

### Light and presence sensor



Option supplied under request.

### Security screwdriver bit



Security screwdriver bit

Order code  
**926000**

### Emergency unit




Emergency unit 3 hours  
Emergency unit 1 hour

Order code  
**K3**  
**K1**


• Test function by telecommand signal.

### PHOTOMETRY


### DIMENSIONS



**ZLP /C LED 42W**  
**DOZ 4000K**



**ZLP /C LED 52W**  
**DOZ 4000K**



### TO SPECIFY:

Corner vandal proof LED luminaire with IP65/IK10. Opal 3mm polycarbonate diffuser, tamperproof screws and polyurethane foam gasket. Designed to resist to extreme mechanical impacts (IK10, 170 Joules). Standard version with 4000K, CRI>80 and 50000h life time (@L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, anti-graffiti protective coating, anti-sticker protective coating and 1 or 3 hours emergency unit. - as Roxo Lighting ZLP /C LED

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.